


Lamine IGHIL AMEUR^{*1}, Lucile SAUSSAYE¹, David MATHON²

¹Cerema - Direction Territoriale Normandie-Centre, Blois, France
²Direction Départementale des Territoires du Loir-et-Cher, Blois, France
^{*}lamine.ighil-ameur@cerema.fr


Damages induced by shrinkage-swelling phenomenon of clayey soils are well known as major natural disaster in France and more generally in the world. Affecting an individual house, soil shrinkage-swelling causes important and expensive structural damages. For this case, Cerema has tested an innovative and environmental solution on one damaged-house localized at center region in France. It is based on stocking rainwater into two tanks of 800 liters volume capacity of each one and the principle is to humidify the foundation soil during high drying period.

1- Description and initial investigations

➤ House localization and description



➤ Cracking state since 2015



➤ Geotechnical investigations




➤ Soil physical properties


Localization	Particle size distribution			Dmax (mm)	VSI (g/100 g of dry soil)	Plasticity Index PI (%)	
	2 μm	80 μm	2 mm				
Excavator drilling	57	97	99	10	/	37	
Decalcification clay	SP1 (1.5 m)	/	98	99	5	5.5	39
	SP2 (1 m)	/	98	100	5	6.4	/
Beauce limestone	SP1 (5 m)	/	89	98	10	6.0	/
	SP1 (5 m)	/	58	84	20	1.4	/

2- Rainwater storage and injection process


➤ Rainwater collection and storage



➤ Injection device and monitoring




➤ Injection points location




3- Tensiometric, crack and hygrometric monitoring


➤ Tensiometric probe



➤ Monitoring of house existing cracks



➤ Monitor®



➤ Air temperature and humidity measurement



4- MACH follow-up operations

➤ Principal operations to follow-up during the MACH process:

(2) Cracks monitoring




(1) Soil suction monitoring: this operation allows recording the soil suctions related to water content conditions, and can reach a maximum suction of 239 kPa which represents the limit of tensiometric probes.

(1) Tensiometric monitoring



(3) Temperature and humidity measurement



(2) Cracking monitoring: it consists of measuring the opening or the closing of the existing cracks.


(3) Since the end of 2018, a connected device has been installed in the house to measure in real time and continuously relative humidity and temperature of the outside atmosphere.

5- Experimental results: comparison between 2017 and 2018


➤ Rainfall and temperature data from meteorological Blois station (41)

Year 2017

Year 2018



➤ Soil suction curves of the corresponding probes and evolution of the street facade crack (red curve)



6- Conclusions

- This study summarizes the MACH monitoring operations during 2018 and a comparison is made with 2017's results.
- Summer of 2018 was considered as one of the hottest and comparable to that of 2003, resulting in a particularly severe drought. This made it possible to test the MACH process under extreme demands of rainwater and strong suctions in the soil.
- The results obtained confirm the effectiveness of the MACH process for the stabilization of cracks during the period of high temperatures and very low rainfall.

ACKNOWLEDGEMENT:

This work is funded by la Direction Générale de la Prévention des Risques of Ministère de la Transition Écologique et Solidaire. The authors would like to thank the MACH house owner, Mr. Noblecourt, for his availability to do the rainwater injections. Then, additional thanks to the industrial partners for their contribution to the instrumentation of the house and to take part to the follow-up phase: Agence Qualité Construction (AQC); ELEX expert society and Challenge Agriculture society.

REFERENCES:

- BRGM, 2019. "Géosciences et risques naturels", the BRGM review for sustainable land No: 23, pp50-57.
- CCR, 2018 "Impact du changement climatique sur les dommages assurés", Scénario RPC 8.5, Report of a study available online: www.catastrophes-naturelles.ccr.fr.
- Mathon D., Dore L., Ighil Ameur L., 2018 "Réparer une maison en arrosant ses fondations - Le projet MACH". JNGG, 13-15 June 2018, Champs-sur-Marne, France.
- Mathon D., Ighil Ameur L., Dore L., Saussaye L., 2018 "Réparer une maison en arrosant ses fondations - Projet MACH". Fourth International Conference UNSAT, 29-31 October 2018, Oran, Algeria.