

# Los Angeles Light Rail Transit

*Then and Now*



Metro

# Bienvenue à Los Angeles

*Los Angeles has a rich history of Light Rail Transit (LRT) service, which emerged from the Interurban and Tram systems of the early twentieth century to the Metro Rail system of today. This presentation will provide the following:*

- An overview of Los Angeles LRT then and now*
- A case example of LRT policy and project development by Los Angeles Metro*
- Discussion regarding Urban Insertion topics in the case study example*



**Metro**

# Los Angeles, California

## *Then and Now*



Located on the west coast of the United States of America

Part of the Southern California Region

Los Angeles County is 4083 square miles/10575 square kilometers

88 municipalities


9.8 million people



Metro

# Light Rail Transit Then

## *Pacific Electric Railway*



Service from 1901 to 1961

World's largest system with 1167 route miles/1878 route kilometers

2160 daily trains  
10,000 daily trains in World War II



Metro

# Light Rail Transit Then

## *Pacific Electric Railway*



Used many different types of interurban and street tram vehicles  
Electric power using trolley wire



Invented the “wig wag” crossing signal



Metro

# Light Rail Transit Then


*Pacific Electric Railway*



Metro

# Light Rail Transit Now

## Los Angeles County Metropolitan Transportation Authority



Formed in 1993 via a merger of two agencies

Urban bus and urban rail service, with heavy rail transit and light rail transit

2438 buses

1433 square mile/3711 square kilometer service area

105 route miles/168 route kilometers of Metro Rail service

93 stations

1.1 million daily boardings



Metro

# Light Rail Transit Now

*Los Angeles County Metropolitan Transportation Authority*



Railway/city  
line operations  
in Metro Rights  
of Way

High floor  
vehicles with up  
to three car  
consists



Metro



# Light Rail Transit Now

*Los Angeles County Metropolitan Transportation Authority*



Limited street  
running  
operations

Electric power  
using pantograph  
and overhead  
contact system

Stations  
accommodate  
high floor light  
rail vehicles



Metro

# Exposition Corridor Case Study

Los Angeles County Metropolitan Transportation Authority



Downtown Los Angeles to Downtown Santa Monica

# Mid-City Segment

## *Exposition Corridor*



Metro

# Mid-City Segment

## *Exposition Corridor*



Metro

# Grade Crossing Policy

## *Exposition Corridor*


*The Grade Crossing Policy is intended to provide a structured process for the evaluation of potential grade separations vs. at grade operation along light rail lines. The policy recognizes the operational and safety issues of at-grade versus grade-separated solutions as well as the institutional and monetary implications. It is recognized that local, state and federal government officials are involved in the process as well as the communities along the light rail line.*

- Developed as a response to concerns regarding both cross street vehicular safety and pedestrian crossing safety.*
- Accident statistics along other rail lines were cited as cause for concern, particularly in areas where the line passes in close proximity to schools, parks and other community facilities.*
- Special studies were conducted to identify best practices for light rail safety to inform the design of the Mid-City/Exposition project.*




# Grade Crossing Policy

## Exposition Corridor – Light Rail Crossing Review Process



# Grade Crossing Policy

## Exposition Corridor – Grade Crossing Review Methodology



*The results of the initial screening in Milestone 1 will result in one of three outcomes:*


- *At Grade Operation should be feasible*
- *Possible At Grade Operation*
- *Grade Separation Usually Required*



Metro

# Grade Crossing Policy

## Exposition Corridor – Nomograph of Initial Screening





# Grade Crossing Policy

## *Exposition Corridor – Safety Concerns and Potential Mitigation*

<u>Safety Concern</u>	<u>Mitigation</u>
Traffic Queuing	Anti-Queuing Traffic Control Measures; Grade Separation if None Feasible
Approach and Corner Sight Distance	Supplemental Active Warning Devices Reduce Allowable Train Speed
Visual Confusion/Sign or Signal Clutter	Removal of Unnecessary Signs/Signals
Prevailing High Traffic Speed	Control Traffic Speed with Traffic Signal Control or Enforcement
Large Truck Percentage	Restrict Truck Traffic. Improve Signing or Traffic Signal Timing to Keep Trucks Off Tracks
Heavy Pedestrian Volumes	Channelization, Active Warning Devices and Pedestrian Control Devices, Traffic Control Officers for Events
School Access Route	Channelization, Active Warning Devices and Pedestrian Control Devices, Education, and Crossing Guards
Emergency Vehicle Route	Identify and/or Provide Alternative Route Provide Remote Notification of Crossing Status
Accident History	Remedy Specific to the Accident Cause
Gate Drive Around Potential	Photo Enforcement, Medians, Four Quadrant Gates
Delineation and Roadway Marking	Increase Contrast at Crossing or Improve Delineation
Traffic Control Observance	Install Active Signs. Increase Enforcement


*Safety concerns and potential mitigation will emerge as the result of the Initial Screening*



**Metro**

# Street Running


## *Exposition Corridor Mid-City Segment*



Metro

# Street Running

## Exposition Corridor Mid-City Segment



Station Area



At USC Exposition Park



Project Alignment



Metro

# Street Running

*Exposition Corridor Mid-City Segment*



Metro



# Street Running


## Exposition Corridor Mid-City Segment



Station Area



At Vermont Station




Project Alignment



Metro

# Street Running


## Exposition Corridor Mid-City Segment



Station Area



At Western Station



Metro

# Street Running

## *Exposition Corridor Mid-City Segment*



*Median Running*



*Between Western Station and Gramercy Place*



*Side Running*



*Class 2 Bike Lane*

*LRT Guideway*

*Class 2 Bike Lane*

*Site Plan*

*Removal of two vehicular traffic lanes to allow for double track LRT alignment, bike lanes and transit parkway*



**Metro**



# Multimodal Safety, At-Grade Crossings

## *Exposition Corridor Mid-City Segment*



A variety of techniques are available for enhancing pedestrian safety at light rail at-grade crossings.

The Project incorporates passive signing, pavement marking, and barrier channelization, including active warning devices, swing gates, and pedestrian gates into its pedestrian safety approach.



Metro

# At-Grade Crossings, Signals and Gate Protection

## *Exposition Corridor Mid-City Segment*



*Four Quadrant Gates, typically located in Cab Signal Segment*



*Bar Signals and other city traffic and transit priority devices*



*Motorist Safety Signals*



Metro

# Standardized Station Design

## *Exposition Corridor*



*Factory Built Modular  
Station Canopies*

*High Floor Platforms with  
under platform refuge area*



**Metro**

# Operations Comparisons

## *Exposition Corridor – Line features and State of California requirements*



### Street Running Operations

- Operations governed by city traffic signal/transit priority control at grade crossings
- Non gated grade crossings
- LRT operations at 35 miles per hour/56 kilometers per hour or lower
- Green band transit signal priority to enable nonstop operations from station to station



### Cab Signal Operations

- Operator call the gates down at each grade crossing
- Operations governed by railroad signal control
- Gated grade crossings
- LRT operations above 35 miles per hour/56 kilometers per hour
- Used in either pre-emption or priority mode



**Metro**

# Summary

## *Exposition Corridor Mid-City Segment*

- Street running operations for five miles from Downtown Los Angeles to Gramercy Place
- Grade Crossing Policy determined that out of 27 grade crossings, three crossings were warranted for grade separation
- Removal of two traffic lanes due to existing low traffic volume allows for double track LRT alignment and parkway
- Class 2 bike lanes built parallel to LRT alignment
- Signal and train delays due to frequent station stops from Vermont eastbound to Downtown Los Angeles
- Less signal priority than anticipated upstream and complications from having a downtown terminal resulted in slower speeds and delay
- Forty one accidents in the entire corridor from 2014 to 2017
- Out of the total, 19 accidents occurred in the Mid-City segment from Flower St. to Gramercy Place, 13 were Metro and vehicle collisions, and 6 were Metro and pedestrian collisions



# Vision for the future



*I look forward to your input on lessons learned for Urban Insertion best practices for Light Rail Transit*



Metro

# Merci



**Thank  
You!**

Anthony Loui  
Metro Operations Liaison Office  
Los Angeles Metro  
One Gateway Plaza  
Los Angeles, California 90012-2952 USA  
+1 213-418-3273  
[louia@metro.net](mailto:louia@metro.net)



**Metro**